



www.maxforklift.com

Productive & Efficient

AA SERIES

1.5-3.5 TON



AA Series Electric Counterbalance Forklift Truck



maximal



No. 1, Jinxin Road, Lushan Street, Fuyang District, Hangzhou City, Zhejiang Province, China

Sales hotline: 86-571-28037691 Sales email: angela@maxforklift.com
After-sales e-mail: China-OverseasServices@hyster-yale.com


All rights reserved. If you have any questions, please contact us.



AA SERIES Product Features

Comfort

- The upgraded gear pump reduces the output pressure and ensures the high efficiency of the hydraulic system.
- The output pulse is 4 times lower than the standard gear pump, with the noise reduced by 15dB.



- Optimized the ergonomic design, improve the operating comfort, reduce the driver's fatigue for long working hours.




Reliability

- The PM controller can keep the working temperature below 60°C, improving the service life of the motor and controller.
- The protection grade reaches IP65, compared with common AC forklift, the service time can be extended by about 20%.



High efficiency

- Maximum speed for permanent magnet synchronous motor is up to 6500 RPM.
- More suitable for frequent starting and stopping operation conditions, the high efficiency is the main factor to reduce energy consumption.
- High efficiency motor up to 95%



Safety

- Integrated taillight protection cover, no need for disassembly, improves the protection level for lights.



AA SERIES Specification Parameters

Features	1.1	Manufacturer		HYM	HYM	HYM	HYM	HYM	HYM
	1.2	Model		FBA15-YJ	FBA18-YJ	FBA20-YJ	FBA25-YJ	FBA30-YJ	FBA35-YJ
	1.3	Power source: battery		Battery	Battery	Battery	Battery	Battery	Battery
	1.4	Operating mode: seated		Seated	Seated	Seated	Seated	Seated	Seated
	1.5	Load rating	Q (kg)	1500	1800	2000	2500	3000	3500
	1.6	Load center	c (mm)	500	500	500	500	500	500
	1.8	Front overhang	x (mm)	410	410	454	454	495.5	495.5
	1.9	Wheelbase	y (mm)	1380	1380	1485	1485	1690	1690
Weight	2.1	Unloaded vehicle weight	kg	3125	3450	4240	4390	5070	5540
	2.2	Front/rear axle full load	kg	4260 / 355	4870 / 400	5600 / 650	6430 / 470	7500 / 570	8400 / 700
	2.3	Front/rear axle empty load	kg	1590 / 1560	1700 / 1760	1850 / 2390	2130 / 2270	2190 / 2890	2600 / 2940
Wheels and tires	3.1	Tire: inflatable, solid, superplasticity		L	L	L	L	L	SE
	3.2	Tire size, front		6.00-9 10PR	6.00-9 10PR	23x9-10 16PR	23x9-10 16PR	23x9-10 16PR	23x9-10 16PR
	3.3	Tire size, rear		5.00-8 8PR	5.00-8 8PR	18x7-8 14PR	18x7-8 14PR	18x7-8 14PR	18x7-8 14PR
	3.5	Number of wheels, front/rear (X=drive)		2x / 2	2x / 2	2x / 2	2x / 2	2x / 2	2x / 2
	3.6	Tread, front wheel	b ₁₀ (mm)	955	955	1058	1058	1124	1124
	3.7	Tread, rear wheel	b ₁₁ (mm)	920	920	960	960	1010	1010
		3.8	Number of wheels, front/rear (X=drive)		2x / 2	2x / 2	2x / 2	2x / 2	2x / 2
Size	4.1	Mast tilting angle, front/rear	degrees	5 / 10	5 / 10	5 / 10	5 / 10	5 / 10	5 / 10
	4.2	Mast retracted height	h ₁ (mm)	2000	2000	2015	2015	2120	2120
	4.3	Free lift height	h ₂ (mm)	135	135	140	140	165	165
	4.4	Fork lift height	h ₃ (mm)	3000	3000	3000	3000	3000	3000
	4.5	Maximum mast extended height	h ₄ (mm)	3980	3980	3980	3980	3980	3980
	4.7	Height of overhead guard	h ₆ (mm)	2155	2155	2152	2152	2138	2138
	4.8	Seat height	h ₇ (mm)	1080	1080	1080	1080	1080	1080
	4.12	Height of traction pin	h ₁₀ (mm)	290	290	250	250	270	270
	4.19	Overall length of the truck	l ₁ (mm)	2993	2993	3356.5	3356.5	3709	3709
	4.20	Length to the fork face	l ₂ (mm)	2073	2073	2286.5	2286.5	2639	2639
	4.21	Overall width of the truck	b ₁ (mm)	1120	1120	1285	1285	1365	1365
	4.22	Fork size	s/e/l (mm)	35 / 100 / 920	35 / 100 / 920	40 / 122 / 1070	40 / 122 / 1070	50 / 122 / 1070	50 / 122 / 1070
	4.23	Mounting grade of carriage		ISO2328 2A	ISO2328 2A	ISO2328 2A	ISO2328 2A	ISO2328 3A	ISO2328 3A
	4.24	Carriage width	b ₃ (mm)	1040	1040	1040	1040	1100	1100
	4.25	Outer fork spacing	b ₅ (mm)	200 / 890	200/890	1000	1000	1060	1060
	4.31	Mast ground clearance, loaded	m ₁ (mm)	95	95	65	65	80	80
	4.32	Wheelbase center ground clearance	m ₂ (mm)	105	105	95	95	83	83
	4.33	Aisle width, tray size: 1000mm (length) x1200mm (width)	Ast (mm)	3541	3541	3732	3732	4101	4101
	4.34	Aisle width, tray size: 1200mm (length) x800mm (width)	Ast (mm)	3741	3741	3932	3932	4301	4301
4.35	Outer turning radius	Wa (mm)	1965	1965	2080	2080	2405	2405	
4.36	Inner turning radius	b ₁₃ (mm)	703	703	599	599	815	815	
Performance	5.1	Driving speed, loaded/unloaded	km/h	15 / 16	15 / 16	15 / 16	15 / 16	15 / 16	15 / 16
	5.2	Lifting speed, loaded/unloaded	mm/s	290 / 440	290 / 440	280 / 400	280 / 400	280 / 410	280 / 410
	5.3	Lowering speed, loaded/unloaded	mm/s	334 / 297	334 / 297	375 / 372	375 / 372	461 / 412	461 / 412
	5.6	Maximum traction force (5 minutes), loaded/unloaded	N	11550 / 10410	11550 / 10410	15530 / 14410	15530 / 14410	19000 / 11000	19000 / 11000
	5.7	Gradeability (30 minutes), loaded/unloaded	%	15	15	15	15	15	15
	5.9	Accelerating time (10m), loaded/unloaded	sec	5.71 / 5.65	5.71 / 5.65	5.29 / 4.91	5.29 / 4.91	5.48 / 5.42	5.48 / 5.42
5.10	Service brake		Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	
Motor	6.1	Driving motor, rated output power	kW	9.5	9.5	12.5	12.5	15.5	15.5
	6.2	Lift motor, rated output power	kW	11	11	14	14	16	16
Battery parameters	6.4	Volt/Ah (5 hours)	V/Ah	83.2 / 173	83.2 / 173	83.2 / 230	83.2 / 230	80 / 346	80 / 346
	6.5	Battery weight	kg	230±10	230±10	290±10	290±10	500±10	500±10
	6.5.1	Battery size	l/w/h (mm)	980 / 465 / 506	985 / 465 / 750	1028 / 503 / 490	1028 / 503 / 490	1028 / 680 / 600	1028 / 680 / 600

AA SERIES FBA15-18 Electric forklift truck mast

Model	Maximum Fork Height (mm)	Mast Height						Free Lift Height		Load Distance (mm)		Mast Tilt (Deg)	
		Overall Lowered Height (mm)		Extended Height				Without Load Backrest (mm)	Load Backrest (mm)	1.5t	1.8t	FWD	Back
				Without Load Backrest (mm)		Load Backrest (mm)							
2 LFL mast	3000	1990	1990	3513	3513	3984	3984	135	135	410	410	5	10
	3300	2140	2140	3813	3813	4284	4284	135	135	410	410	5	10
	3500	2240	2240	4013	4013	4484	4484	135	135	410	410	5	10
	3700	2340	2340	4213	4213	4684	4684	135	135	410	410	5	10
	4000	2540	2540	4513	4513	4984	4984	135	135	410	410	5	10
	4500	2790	2790	5013	5013	5484	5484	135	135	410	410	5	6
2 FFL mast	3000	1990	1990	3513	3513	3984	3984	1486	1015	410	410	5	10
	3300	2140	2140	3813	3813	4284	4284	1636	1165	410	410	5	10
	3500	2240	2240	4013	4013	4484	4484	1736	1265	410	410	5	10
	3700	2340	2340	4213	4213	4684	4684	1836	1365	410	410	5	10
	4000	2540	2540	4513	4513	4984	4984	1936	1465	410	410	5	10
	4500	2790	2790	5013	5013	5484	5484	2036	1565	410	410	5	6
3 FFL mast	4800	2140	2140	5313	5313	5784	5784	1616	1145	410	410	5	6
	5000	2240	2240	5513	5513	5984	5984	1716	1245	410	410	5	6
	5500	2405	2405	6013	6013	6484	6484	1886	1415	410	410	3	6
	6000	2590	2590	6513	6513	6984	6984	2066	1595	410	410	3	6

AA SERIES FBA20-25 Electric forklift truck mast

Model	Maximum Fork Height (mm)	Mast Height						Free Lift Height		Load Distance (mm)		Mast Tilt (Deg)	
		Overall Lowered Height (mm)		Extended Height				Without Load Backrest (mm)	Load Backrest (mm)	2t	2.5t	FWD	Back
				Without Load Backrest (mm)		Load Backrest (mm)							
2 LFL mast	3000	2030	2030	3615	3615	4015	4015	140	140	454	454	5	10
	3300	2180	2180	3915	3915	4315	4315	140	140	454	454	5	10
	3500	2280	2280	4115	4115	4515	4515	140	140	454	454	5	10
	3700	2380	2380	4315	4315	4715	4715	140	140	454	454	5	10
	4000	2580	2580	4615	4615	5015	5015	140	140	454	454	5	10
	4500	2830	2830	5115	5115	5515	5515	140	140	454	454	5	6
2 FFL mast	3000	2030	2030	3615	3615	4015	4015	1385	985	477	477	5	10
	3300	2180	2180	3915	3915	4315	4315	1535	1135	477	477	5	10
	3500	2280	2280	4115	4115	4515	4515	1635	1235	477	477	5	10
	3700	2380	2380	4315	4315	4715	4715	1735	1335	477	477	5	10
	4000	2580	2580	4615	4615	5015	5015	1835	1435	477	477	5	10
	4500	2830	2830	5115	5115	5515	5515	1935	1535	477	477	5	6
3 FFL mast	4500	2090	2090	4965	4965	5365	5365	1390	990	490	490	5	6
	4800	2190	2190	5165	5165	5565	5565	1490	1090	490	490	5	6
	5000	2290	2290	5365	5365	5765	5765	1590	1190	490	490	5	6
	5500	2455	2455	6115	6115	6515	6515	1800	1400	490	490	3	6
	6000	2640	2640	6615	6615	7015	7015	1990	1590	490	490	3	6


AA SERIES FBA30 Electric forklift truck mast

Model	Maximum Fork Height (mm)	Mast Height				Free Lift Height		Load Distance (mm)	Mast Tilt (Deg)	
		Overall Lowered Height (mm)	Extended Height		Without Load Backrest (mm)	Load Backrest (mm)	FWD		Back	
			Without Load Backrest (mm)	Load Backrest (mm)						
2 LFL mast	3000	2045	3670	4140	165	165	475	5	10	
	3300	2195	3970	4440	165	165	475	5	10	
	3500	2295	4170	4640	165	165	475	5	10	
	3700	2395	4370	4840	165	165	475	5	10	
	4000	2595	4670	5140	165	165	475	5	10	
	4500	2845	5170	5640	165	165	475	5	6	
2 FFL mast	3000	2045	3685	4140	1390	935	490	5	10	
	3300	2195	3985	4440	1540	1085	490	5	10	
	3500	2295	4185	4640	1640	1185	490	5	10	
	3700	2395	4385	4840	1740	1285	490	5	10	
3 FFL mast	4000	1920	4725	5140	1215	800	500	5	6	
	4350	2045	5075	5490	1340	925	500	5	6	
	4500	2095	5225	5640	1390	975	500	5	6	
	4800	2195	5525	5940	1490	1075	500	5	6	
	5000	2295	5725	6140	1590	1175	500	5	6	
	5500	2460	6225	6640	1745	1330	500	3	6	
	6000	2645	6725	7140	1940	1525	500	3	6	

AA SERIES FBA35 Electric forklift truck mast

型号	Maximum Fork Height (mm)	Mast Height				Free Lift Height		Load Distance (mm)	Mast Tilt (Deg)	
		Overall Lowered Height (mm)	Extended Height		Without Load Backrest (mm)	Load Backrest (mm)	FWD		Back	
			Without Load Backrest (mm)	Load Backrest (mm)						
2 LFL mast	3000	2120	3740	4140	170	170	495	5	10	
	3300	2270	4040	4440	170	170	495	5	10	
	3500	2370	4240	4640	170	170	495	5	10	
	3700	2470	4440	4840	170	170	495	5	6	
	4000	2670	4740	5140	170	170	495	5	6	
	4500	2920	5240	5640	170	170	495	5	6	
2 FFL mast	3000	2120	3725	4140	1415	1000	505	5	10	
	3300	2270	4025	4440	1565	1150	505	5	10	
	3500	2370	4225	4640	1665	1250	505	5	10	
3 FFL mast	3700	2470	4425	4840	1765	1350	505	5	6	
	4000	1995	4810	5140	1205	875	522	5	6	
	4350	2120	5160	5490	1330	1000	522	5	6	
	4500	2170	5310	5640	1380	1050	522	5	6	
	4800	2270	5610	5940	1480	1150	522	5	6	
	5000	2370	5810	6140	1580	1250	522	5	6	
	5500	2535	6310	6640	1735	1405	522	3	6	
	6000	2720	6810	7140	1930	1600	522	3	6	

AA SERIES FBA15-35 Electric forklift truck mast



AA SERIES FBA15-35 Specification

